


NOTES - ALL RESISTORS IN OHMS 1/2W 10% UNLESS OTHERWISE SPECIFIED.
 - ALL CAPACITORS IN MFD AND 400V 10% UNLESS OTHERWISE SPECIFIED.
 - D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20,000 Ω PER VOLT VOLTMETER.
 - NUMBERS IN PARENTHESIS REFER TO AMPEG'S PART NO.
 * 2A FUSE SHOULD BE IN 240V MODELS ONLY.
 - D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO GROUND UNLESS OTHERWISE SPECIFIED.
 - CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.
 ** RES. 60, 61, 62, 63 & 64 ARE LOCATED ON SW1.
 * - THE P.T. FOR 240V MODELS HAS BLCK WIRE CONNECTED TO BLUE WH. AS DOTTED LINE SHOWS

POWER AMP.
 P.C. BD.
 NO. 64-60-076

POST OFFICE BOX 515
 925-9700

 LINDEN, NEW JERSEY 07036

MODEL
 B15S
 U.S. PATENT PENDING

DRN. BY	DATE	DWG. NO.	PART NO.	REV.
S. C.	3-71	06400	40102580	C

591717-1