



NOTES.—ALL RESISTORS IN OHMS ½W 10% UNLESS OTHERWISE SPECIFIED.
 —ALL CAPACITORS IN MFD. & 400V UNLESS OTHERWISE SPECIFIED.
 —DC VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20000Ω PER VOLT VOLTMETER.
 —NUMBERS IN PARENTHESIS REFER TO AMPEGS PART NO.
 —PARTS DESIGNATED BY * ARE IN 240V MODELS ONLY. THE P.T. FOR 240V MODELS HAS BLCK. WIRE CONNECTED TO BLUE WIRE
 —D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO CHASSIS GROUND UNLESS OTHERWISE SPECIFIED.
 —CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.
 —D7-10 ARE SILICON AX TYPE 1AMP 1400 VOLTS DIODES.

MAGNAVOX NO. 591714-1
 POST OFFICE BOX 515
ampeg
 LINDEN, NEW JERSEY 07036

MODEL V2
 US. PATENT PENDING.

DRN BY	DATE	DWG. NO.	PART NO.	REV.
ew	6.71	06800	4010268	C