

CLASSIC SERIES

HEADS

COMPARISON CHART



	SVT®-CL	V-4B
Tone Controls	Bass, Midrange, Treble	Bass, Midrange, Treble
Midrange Selector	(1) 220Hz, (2) 450Hz, (3) 800Hz, (4) 1.6kHz, (5) 3kHz	3-Position Rocker Switch: 220Hz, 800Hz, 3kHz
Boost(s)	Ultra Hi/Ultra Lo	Ultra Hi/Ultra Lo
Preamp Out/Power Amp In	1/4"	1/4"
Ext Amp Out	1/4"	1/4"
Line Out Ground Lift	NA	Switch
Power	IEC	IEC
Preamp Tubes	(2) 12AX7	(2) 12AX7
Driver Tubes	(1) 12AX7 (2) 12AU7	(1) 12AX7 (1) 12AU7
Power Amp Tubes	(6) 6550	(4) 6L6GC
Discreet Channels	One	One
RMS Power Output	300W	100W
Input Options	0dB, -15dB	0dB, -15dB
Gain Control	Yes	Yes
Master Volume	Yes	Yes
Line Output	Transformer Balanced XLR	Balanced XLR
Line Out Pre/Post EQ	NA	NA
Line Out Level	NA	NA
Power Amp Bias Control	1 and 2	NA
Impedance Selector	2Ω/4Ω	NA
Extension Speaker Outputs	(2) 1/4" (1) Neutrik® speakON®	(1) 8Ω 1/4" (2) 4Ω 1/4" (2) 2Ω 1/4"
Product Weight (lb/kg)	80/36.3	41/18.6

All specifications subject to change.