



BSE410H Series Bass Cabinets

BSE410H



BSE410HS



BSE410HLF

Please read this user's guide prior
to using your new enclosure.



Ampeg BSE410H Series Bass Cabinets

Ampeg BSE410H Series 4x10 Bass Cabinets are quality two-way speaker cabinets suitable for all venue sizes.

The cabinets feature heavy duty recessed handles, removable casters, and a heavy gauge steel grill for maximum speaker protection.

The jackplate features two 1/4" jacks wired in parallel, allowing easy daisy chaining from one speaker to another. Each of the jacks may be used as an input or a through connection. The three position HF Horn switch allows for:

- Full high frequency output (0 setting)
- -6dB reduction of the high frequencies through the horn (-6 setting)
- Horn shutoff (off setting)


IMPORTANT SAFETY INSTRUCTIONS:

1. Read, follow and keep these instructions. Heed all warnings.
2. This speaker is capable of producing high sound pressure levels that may cause permanent hearing damage. User caution is advised and ear protection is recommended during use.
3. This speaker is designed for use on a level floor or mounted to a properly rated speaker stand with the supplied stand mount adapter. The use of a speaker stand poses a risk of personal injury. Installations should be performed by a professional installer in accordance with local building codes.
4. Speaker cables are a tripping hazard and must be routed out of traffic areas and away from any possible accidental contact.
5. Do not expose this speaker to rain or moisture. Do not place liquid filled containers on this speaker. Clean only with a damp cloth.
6. Repair or service of this speaker should be performed only by qualified personnel.



Ampeg BSE410H Series Bass Cabinets

The BSE410H Series Jackplate:



1: 1/4" Input / Output Jacks

2: High Frequency Horn Level Switch

AMPEG BSE410H

Series Bass Cabinets

TECHNICAL SPECIFICATIONS:

	BSE410H	BSE410HS	BSE410HLF
TYPE	4x10" Bass Enclosure	4x10" Bass Enclosure	4x10" Bass Enclosure
FREQ RESPONSE (+/-3dB)	55Hz – 18kHz	50Hz – 18kHz	50Hz – 18kHz
USABLE LOW FREQ (-10dB)	40Hz	40Hz	36Hz
POWER HANDLING	200W RMS	400W RMS	400W RMS
IMPEDANCE	8 ohms	8 ohms	4 ohms
SENSITIVITY	95dB SPL 1w/1m	98dB SPL 1w/1m	99dB SPL 1w/1m
MAXIMUM SPL	118dB	122dB	125dB
COMPONENTS	4-10" Custom Designed LF Speakers, 1" diaphragm HF Horn	4-10" Special Design LF Speakers, 1" diaphragm HF Horn	4-10" Special Design LF Speakers, 1" diaphragm HF Horn
DIMENSIONS (H x W x D)	22.75" x 22.75" x 17.5"	25.75" x 22.75" x 17.5"	25.75" x 22.75" x 17.5"
WEIGHT	75 lbs.	91 lbs.	91 lbs.

CAUTION: THIS SPEAKER IS CAPABLE OF PRODUCING HIGH SOUND PRESSURE LEVELS. CONTINUED EXPOSURE TO HIGH SOUND PRESSURE LEVELS CAN CAUSE PERMANENT HEARING IMPAIRMENT OR LOSS. USER CAUTION IS ADVISED, AND EAR PROTECTION RECOMMENDED IF UNIT IS OPERATED AT HIGH VOLUME.

Ampeg continually develops new products, as well as improves existing ones. For this reason, the specifications and information in this manual are subject to change without notice.

Ampeg – The Power of Bass



www.ampeg.com

Made with Pride in the U.S.A. by Ampeg

©2003 AMPEG, 1400 Ferguson Avenue, St. Louis, MO 63133 U.S.A.

47-776-01 • 060203

