



DASH NO	C1 & C2	C3	L1	L2
-01	3 uf/50V	---	.3mH	---
-02	2.2uf/100V	6uf/50V	.8mH	1.8mH
-03	2.2uf/100V	6uf/50V	.3mH	1.0mH
-04	3 uf/50V	---	.15mH	---
-05	3 uf/50V	---	.3mH	---

REV	Date	DESCRIPTION	Ecr(s)/Ecn(s)	Chgd By	Appvd by	Date
3	7/30/02	ADDED -05 ASSY	N00923	REM		
2	12-27-01	DEL 30-859-01/30-895-01 ADD 30-015-01	N00727	WFB		
1	9-21-00	ADDED VER 4, CHGD PN OF B1,4 DELETED 4 SPACERS	N00402	WFB		
0	8-31-00	CONTROL ISSUE				

- 4) SEE TABLE FOR VALUES.
- 5) USED ON DASH 01, 04, -05 ONLY.
- 6) SEE BOM FOR USAGE

CAUTION:
THIS SCHEMATIC IS PROVIDED FOR USE BY QUALIFIED PERSONNEL.
TO AVOID RISK OF ELECTRIC SHOCK, REFER SERVICING TO QUALIFIED SERVICE PERSONNEL. DO NOT PERFORM ANY SERVICING BEYOND THAT EXPLAINED IN THE OPERATING INSTRUCTIONS.

- NOTES:
- 1) CAUTION: SHOCK HAZARD!! THIS UNIT CONTAINS HAZARDOUS VOLTAGE. DISCONNECT POWER AND BE SURE POWER SUPPLY IS DISCHARGED BEFORE TOUCHING INTERNAL PARTS.
 - 2) UNLESS NOTED, RESISTOR VALUES IN OHMS, 1/4W-5% TOL. CAPACITOR VALUES IN MICROFARADS, 50V-10% TOL.
 - 3) VOLTAGES ARE MEASURED WITH 1 MEGOHM OSCILLOSCOPE AND 10 MEGOHM DIGITAL VOLTMETER.

Signatures:		Date:	 11880 Borman Drive, St. Louis, MO 63146
Drawn:	RLB	12-13-99	
Checked:			First Used On: PR410
Released:			
Plot Date: Wed Jul 31, 2002	Drawing Size: A	Drawing Title: CROSSOVER	
Plot Time: 10:31:07	Drawing Type: Schematic	Drawing Number: 07S777-XX	
Tolerance:	Class Code: NONE	Sheet 1 of 1	